

SPECIFICA PRODOTTO / TECHNICAL DATA SHEET

FILTRAZIONE / FILTRATION

Stabilimento / Factory:
ORV Misinto



FILTRO GC RETE

<i>MAIN APPLICATIONS</i>	:	<i>PREFILTER FOR AIR TREATMENT IN CONDITIONING AND VENTILATION SYSTEMS.</i>
<i>COMPOSITION</i>	:	<i>PROGRESSIVELY STRUCTURE MEDIA MADE FROM NEEDED PUNCH SYNTHETIC FIBERS, POLYESTER REINFORCEMENT SCRIM</i>
<i>WEIGHT</i>	:	<i>210 grms./sq. meter</i>
<i>THICKNESS</i>	:	<i>8-10 mms.</i>
<i>TEMPERATURE RESISTANCE</i>	:	<i>80°C</i>
<i>HUMIDITY</i>	:	<i>100 % relative humidity</i>

* STANDARD DIMENSIONS

<i>WIDTHS</i>	:	<i>2 meters</i>
<i>LENGTHS</i>	:	<i>20 meters</i>

* TECHNICAL DATA

<i>FRONTAL FILTERING AREA</i>	:	<i>610 x 610 mms.</i>
<i>AIR VELOCITY</i>	:	<i>0.56 mt./sec</i>
<i>AIR FLOW RATE</i>	:	<i>2009 cubic meters/h.</i>
<i>INITIAL PRESSURE DROP</i>	:	<i>22 PA</i>
<i>FINAL PRESSURE DROP</i>	:	<i>250 PA</i>
<i>AVERAGE RESISTANCE A%</i>	:	<i>87 %</i>

* CLASSES

<i>FILTER CLASS</i>	:	<i>G3 DIN 24185 EN 779 (EU 3)</i>
<i>FLAME BEHAVIOUR</i>	:	<i>F1 DIN 53438 TEIL 3 B2 DIN 4102 TEIL 1</i>

AUTHORITY : *MPA NRW- MATERIAL PRUFUNGSAMT NORDRHBIN-WESTFALEN-D*

PRODUCT MANUFACTURED BY : **O.R.V. - ITALY**